

AD-A087 884

FOREIGN TECHNOLOGY DIV WRIGHT-PATTERSON AFB OH
HIGH-VOLTAGE PULSE VOLTAGE GENERATOR; (U)
DEC 79 I I KALYATSKIY, V I KURETS
FTD-ID(RS)T-1972-79

F/G 14/2

UNCLASSIFIED

NL

1 of 1
AD-A087 884




END
DATE
FILMED
9-80
DTIC


PHOTOGRAPH THIS SHEET

ADA087884

DTIC ACCESSION NUMBER



LEVEL



INVENTORY

FTD-ID(RS)T-1972-79

DOCUMENT IDENTIFICATION

DISTRIBUTION STATEMENT A

Approved for public release;
Distribution Unlimited

DISTRIBUTION STATEMENT

ACCESSION FOR	
NTIS	GRA&I <input checked="" type="checkbox"/>
DTIC	TAB <input type="checkbox"/>
UNANNOUNCED <input type="checkbox"/>	
JUSTIFICATION	
BY	
DISTRIBUTION /	
AVAILABILITY CODES	
DIST	AVAIL AND/OR SPECIAL
A	

DISTRIBUTION STAMP

DTIC	
ELECTE	
AUG 15 1980	
S	D
D	

DATE ACCESSIONED

80 6 2 208

DATE RECEIVED IN DTIC

PHOTOGRAPH THIS SHEET AND RETURN TO DTIC-DDA-2

ADA087884

FTD-ID(RS)T-1972-79


FOREIGN TECHNOLOGY DIVISION



HIGH-VOLTAGE PULSE VOLTAGE GENERATOR

by

I. I. Kalyatskiy, V. I. Kurets, and
V. I. Safronov



Approved for public release;
distribution unlimited.



EDITED TRANSLATION

FTD-ID(RS)T-1972-79 21 December 1979

MICROFICHE NR. FTD-80-C-000029

CSF74108190

HIGH-VOLTAGE PULSE VOLTAGE GENERATOR

By: I. I. Kalyatskiy, V. I. Kurets, and
V. I. Safronov

English pages: 2

Source: USSR Patent Nr. 318149, 19 October
1971, pp. 1-2.

Country of origin: USSR

Translated by: Randy Dorsey

Requester: FTD/TQTD

Approved for public release; distribution
unlimited.

THIS TRANSLATION IS A RENDITION OF THE ORIGINAL FOREIGN TEXT WITHOUT ANY ANALYTICAL OR EDITORIAL COMMENT. STATEMENTS OR THEORIES ADVOCATED OR IMPLIED ARE THOSE OF THE SOURCE AND DO NOT NECESSARILY REFLECT THE POSITION OR OPINION OF THE FOREIGN TECHNOLOGY DIVISION.

PREPARED BY:

TRANSLATION DIVISION
FOREIGN TECHNOLOGY DIVISION
WP.AFB, OHIO.

U. S. BOARD ON GEOGRAPHIC NAMES TRANSLITERATION SYSTEM

Block	Italic	Transliteration	Block	Italic	Transliteration
А а	<i>А а</i>	A, a	Р р	<i>Р р</i>	R, r
Б б	<i>Б б</i>	B, b	С с	<i>С с</i>	S, s
В в	<i>В в</i>	V, v	Т т	<i>Т т</i>	T, t
Г г	<i>Г г</i>	G, g	У у	<i>У у</i>	U, u
Д д	<i>Д д</i>	D, d	Ф ф	<i>Ф ф</i>	F, f
Е е	<i>Е е</i>	Ye, ye; E, e*	Х х	<i>Х х</i>	Kh, kh
Ж ж	<i>Ж ж</i>	Zh, zh	Ц ц	<i>Ц ц</i>	Ts, ts
З з	<i>З з</i>	Z, z	Ч ч	<i>Ч ч</i>	Ch, ch
И и	<i>И и</i>	I, i	Ш ш	<i>Ш ш</i>	Sh, sh
Й й	<i>Й й</i>	Y, y	Щ щ	<i>Щ щ</i>	Shch, shch
К к	<i>К к</i>	K, k	Ъ ъ	<i>Ъ ъ</i>	"
Л л	<i>Л л</i>	L, l	Ы ы	<i>Ы ы</i>	Y, y
М м	<i>М м</i>	M, m	Ь ь	<i>Ь ь</i>	'
Н н	<i>Н н</i>	N, n	Э э	<i>Э э</i>	E, e
О о	<i>О о</i>	O, o	Ю ю	<i>Ю ю</i>	Yu, yu
П п	<i>П п</i>	P, p	Я я	<i>Я я</i>	Ya, ya

*ye initially, after vowels, and after ъ, ь; e elsewhere.
When written as ë in Russian, transliterate as yë or ë.

RUSSIAN AND ENGLISH TRIGONOMETRIC FUNCTIONS

Russian	English	Russian	English	Russian	English
sin	sin	sh	sinh	arc sh	sinh ⁻¹
cos	cos	ch	cosh	arc ch	cosh ⁻¹
tg	tan	th	tanh	arc th	tanh ⁻¹
ctg	cot	cth	coth	arc cth	coth ⁻¹
sec	sec	sch	sech	arc sch	sech ⁻¹
cosec	csc	csch	csch	arc csch	csch ⁻¹

Russian	English
rot	curl
lg	log

HIGH-VOLTAGE PULSE VOLTAGE GENERATOR

Authors of the invention: I. I. Kalyatskiy, V. I. Kurets, and V. I. Safronov

Well-known are pulse voltage generators which employ the Arkad'yev-Marx principle of multiplication, increased actuation frequency, the charging of the capacitor batteries of which is accomplished by way of a current-limiting inductance coil.

In the proposed device, in order to increase the threshold actuation frequency, each spark interstage discharger of the generator is of the three electrode version, the center electrode of which is connected via an inductance coil to ground.

In the illustration is shown an electrical diagram of the proposed pulse voltage generator.

The generator consists of a step-up transformer 1, rectifier assembly 2, current limiter coil 3, capacitive energy accumulators 4, separating inductance coils 5, interstage spark commutators (dischargers) 6.


Each commutator 6 is of the three electrode version, the center electrode of which is connected via an inductance coil to ground. The use of the center electrode makes it possible to separate the discharge gap into two independent discharge gaps P_1

and P_2 .

The generator operates in the following manner. Accumulating capacitors 4 are charged by step-up transformer 1 and rectifier assembly 2 via current limiter coil 3 and separating inductance coils 5. Initially there occurs a flash-over of spark gap P_1 , the potential of the center electrode prior to flash-over of spark gap P_1 is zero, and then there occurs a flash-over of spark gap P_2 , and hereafter the device operates like an ordinary GIN [pulse voltage generator] according to the Arkad'yev-Marx principle.

The Object of the Invention

The high-voltage pulse voltage generator, assembled according to the Arkad'yev-Marx arrangement, each stage of which incorporates reactive elements and commutating three-electrode dischargers, is characterized by the fact that in order to increase the actuation frequency, the center electrode of each of the three-electrode dischargers is connected via an inductance coil to a zero point.



318149

DISTRIBUTION LIST

DISTRIBUTION DIRECT TO RECIPIENT

<u>ORGANIZATION</u>	<u>MICROFICHE</u>	<u>ORGANIZATION</u>	<u>MICROFICHE</u>
A205 DMATC	1	E053 AF/INAKA	1
A210 DMAAC	2	E017 AF/RDXTR-W	1
B344 DIA/RDS-3C	9	E403 AFSC/INA	1
C043 USAMIA	1	E404 AEDC	1
C509 BALLISTIC RES LABS	1	E408 AFWL	1
C510 AIR MOBILITY R&D	1	E410 ADTC	1
LAB/FIO			
C513 PICATINNY ARSENAL	1	FTD	
C53 AVIATION SYS COMD	1	CCN	1
C591 PSTC	5	ASD/FTD/NIIS	3
C619 MIA REDSTONE	1	NIA/PHS	1
D008 NISC	1	NIIS	2
H300 USAICE (USAREUR)	1		
P005 DOE	1		
P050 CIA/CRB/ADD/SD	2		
NAVORDSTA (50L)	1		
NASA/NST-44	1		
AFIT/LD	1		
I.I.I./Code L-389	1		
NSA/1213/TDL	2		